

CentOS 7

(1)

CentOS 7

가

, ,

.

,

,

()

가

.

LVM : Default

가 ,

가

:

LVM

가 ,

xf

1.

(OS

)

```
# ip addr
```

```
# vi /etc/sysconfig/network-scripts/ifcfg-eth0
```

```
. . .
```

```
BOOTPROTO=none
```

```
. . .
```

```
IPV6INIT=no
```

```
IPV6_AUTOCONF=no
```

```
IPV6_DEFROUTE=no
```

```
IPV6_FAILURE_FATAL=no
```

```
IPV6_ADDR_GEN_MODE=stable-privacy
```

```
. . .
```

```
ONBOOT=yes # /
```

```
yes
```

```
IPV6_PRIVACY=no
```

```
IPADDR=192.168.122.243
```

```
NETMASK=255.255.255.0
```

```
GATEWAY=192.168.122.1
```

```
DNS1=8.8.8.8
```

```
DNS2=8.8.4.4
```

```
# systemctl restart network
```

```
# ip addr
```

```
eth0 IP
```

```
# ping -c 4 google.com #
```

```
--- google.com ping statistics ---
```

```
4 packets transmitted, 4 received, 0% packet loss, time 3094ms
```

```
rtt min/avg/max/mdev = 82.692/83.010/83.554/0.492 ms
```

2.

```
CentOS 7 timedatectl , .
```

```
# timedatectl
```

```
RTC time :
```

```
NTP enabled : NTP
```

```
NTP synchronized : NTP
```

```
RTC in local TZ : RTC Time zone
```

```
# timedatectl list-timezones | grep -i Asia*
```

```
# timedatectl set-timezone Asia/Seoul
```

```
# timedatectl
```



```
# ps -ef | grep sshd
# systemctl enable sshd

# vi /etc/ssh/sshd_config
. . .
PermitRootLogin=no
. . .

# systemctl restart sshd
```

6.

```
# vi /etc/profile.d/timeout.sh
TMOUT=600
export TMOUT

chmod +x /etc/profile.d/timeout.sh

# source /etc/profile
# echo $TMOUT
600
```

7.

history

```
# vi /etc/profile.d/history.sh

HISTTIMEFORMAT="%F %T -- "
export HISTTIMEFORMAT

# chmod 644 /etc/profile.d/history.sh
```

```
# source /etc/profile.d/history.sh
```

```
# hisotry
```

```
999 2022-04-06 14:50:10 -- vi /etc/profile.d/history.sh
1000      2022-04-06 14:50:19 -- chmod 644
/etc/profile.d/history.sh
1001 2022-04-06 14:50:28 -- source /etc/profile.d/history.sh
1002 2022-04-06 14:50:30 -- history
```

8.

```
# localectl
```

```
System Locale: LANG=en_US.UTF-8
```

```
VC Keymap: us
```

```
X11 Layout: us
```

```
# localectl list-locales | grep -i kr
```

```
ko_KR
```

```
ko_KR.euckr
```

```
ko_KR.utf8
```

```
# localectl set-locale LANG=ko_KR.UTF-8
```

```
# localectl set-keymap kr
```

```
# localectl set-x11-keymap kr
```

```
# localectl
```

```
System Locale: LANG=ko_KR.UTF-8
```

```
VC Keymap: kr
```

```
X11 Layout: kr
```